

1.5-2T Electric Pallet Truck Lithium Battery

CBD15Li / CBD18Li / CBD20Li



SPECIFICATIONS

Characteristics	1.1	Manufacturer	Unit	JAC									
	1.2	Model		CBD15Li				CBD18Li				CBD20Li	
	1.3	Power unit		electric				electric				electric	
	1.4	Operation		pedestrian				pedestrian				pedestrian	
	1.5	Rated traction weight	kg	1500				1800				2000	
	1.6	Load centre	mm	600				600				600	
	1.7	Axle centre to fork face	mm	944				944				944	
	1.8	Wheel base	mm	1243				1243				1243	
Weights	2.1	Service weight with battery	kg	156				142				146	
Wheels/Tyres	3.1	Wheels type		PU				PU				PU	
	3.2	Driving wheel size	Φ×w(mm)	Φ210×70				Φ210×70				Φ210×70	
	3.3	Bearing wheel size	Φ×w(mm)	Φ80×60				Φ80×60				Φ80×60	
	3.4	Wheels, number front/rear (x = driven)		1x/4				1x/4				1x/4	
	3.5	Track width	mm	390/535				400/535				400/535	
Dimensions	4.1	Lift	mm	200				200				200	
	4.2	Overall height (With handle)	mm	610/1212				740/1160				740/1160	
	4.3	Lowered henght	mm	85				85				85	
	4.4	Overall length	mm	1615				1603				1603	
	4.5	Length to fork face	mm	465				453				453	
	4.6	Overall width	mm	550/685				550/685				550/685	
	4.7	Fork dimensions	s/e/l (mm)	50/150/1150				50/150/1150				50/150/1150	
	4.8	Width of forks	mm	550/685				550/685				550/685	
	4.9	Min.Ground clearance	mm	35				35				35	
	4.10	Aisle width with pallet 1000 x 1200 across forks	mm	1815				1804				1804	
	4.11	Aisle width with pallet 800 x 1200 along forks	mm	1865				1854				1854	
	4.12	Min.Turning radius	mm	1405				1398				1398	
Performance	5.1	Travel speed,laden/unladen	km/h	4.2/4.5				4.2/4.5				4.2/4.5	
	5.2	Maximum climbing ability, with/without load	%	5/8				5/10				5/10	
	5.3	Service brake		electromagnetic braking				electromagnetic braking				electromagnetic braking	
Drive/Battery	6.1	Drive motor, 60 minute rating	kW	0.75				0.75				0.75	
	6.2	Lift motor rating at S3 15%	kW	0.8				0.8				0.8	
	6.3	Battery voltage/rated capacity (lithium battery)	V/Ah	24/20	24/30	24/40	24/60	24/20	24/30	24/40	24/60	48/20	48/30
	6.4	Battery weight (± 5%)	kg	6	7.8	10.2	13.2	6	7.8	10.2	13.2	10.2	13.2
Others	7.1	Type of drive control		DC power				DC power				DC power	
	7.2	Noise level at operator's ear	dB(A)	≤70				≤70				≤70	
	7.3	Steering type		Mechanical steering				Mechanical steering				Mechanical steering	

The company reserves the right to change the parameters without notice.