

1.5T Walking Electric Stacker

CDD15



SPECIFICATIONS

Characteristics	1.1	Manufacturer	Unit	JAC						
	1.2	Model		CDD15						
	1.3	Power unit		electric						
	1.4	Operation		pedestrian						
	1.5	Rated traction weight	kg	1500						
	1.6	Load center distance	mm	600						
	1.7	Axle centre to fork face	mm	720						
	1.8	Wheel base	mm	1167						
Weights	2.1	Service weight (with battery)	kg	415	460	477	495	503	515	525
Wheels/Tyres	3.1	Tires		PU						
	3.2	Driving wheel size	Φ×w(mm)	Φ210×70						
	3.3	Bearing wheel size	Φ×w(mm)	Φ80×70						
	3.4	Additional wheels (dimensions)	Φ×w(mm)	Φ115×55						
	3.5	Wheels, number front/rear (x = driven)		1x+1/4						
	3.6	Track width	mm	522						
	3.7	Track width	mm	410/535						
Dimensions	4.1	The max. lifting height	mm	1600	2000	2500	3000	3300	3500	4000
	4.2	Load capacity on Max. height	kg	1500	1300	1100	900	800	700	300
	4.3	Extended mast height	mm	2015	2452	2952	3452	3752	3952	4452
	4.4	Lowered mast height	mm	2015	1495	1745	1995	2145	2245	2495
	4.5	Free lifting height	mm	1600	0	0	0	0	0	0
	4.6	Height of handle in drive position min./max.	mm	700/1225						
	4.7	Lowered fork height	mm	86						
	4.8	Overall length	mm	1740						
	4.9	Length to fork face	mm	590						
	4.10	Overall width	mm	795						
	4.11	Fork dimensions	s/e/l (mm)	60/160/1150						
	4.12	Width of forks	mm	570/695						
	4.13	Min.Ground clearance	mm	26						
	4.14	Aisle width with pallet 1000 x 1200 across forks	mm	2074						
	4.15	Aisle width with pallet 800 x 1200 along forks	mm	2040						
	4.16	Min.Turning radius	mm	1342						
Performance	5.1	Travel speed,laden/unladen	km/h	4.0/4.2						
	5.2	Lifting speed, with/without load	mm/s	92/136						
	5.3	Lowering speed, with/without load	mm/s	112/98						
	5.4	Maximum climbing ability, with/without load	%	6/8						
	5.5	Service brake		electromagnetic braking						
Drive	6.1	Drive motor, 60 minute rating	kW	0.75						
	6.2	Lift motor rating at S3 15%	kW	2.2						
	6.3	Battery according to DIN 43531/35/36 A,B,C,no		no						
	6.4	Battery voltage	V/Ah	2×12/100						
	6.5	Battery weight (± 5%)	kg	2×27						
Others	7.1	Type of drive control		DC power						
	7.2	Noise level at operator's ear	dB(A)	69						
	7.3	Steering type		Mechanical steering						

The company reserves the right to change the parameters without notice.



ADDRESS: SHANGHAI ROAD, BAOHE INDUSTRIAL PARK, HEFEI, ANHUI, CHINA PC. 230051

TEL: 86-551-62297986

FAX: 86-551-62297990

WEB: www.jaczg.com ; www.jacforklift.com

E-mail: jac@jaczg.com

All Rights Reserved by JAC heavy duty co.,ltd. Parameter updating without notice, the picture just for reference. 2020/09/18