

1.6-2T Three-Wheel Electric Counterbalanced Forklift

CPD16SA3 / CPD18SA3 / CPD20SA3





SPECIFICATIONS

Model					CPD16SA3	CPD18SA3	CPD20SA3	
1	Features	Rated load		kg	1600	1800	2000	
2		Load center distance		mm	500	500	500	
3		Lift height		mm	3000	3000	3000	
4		Free lift height		mm	150	150	150	
5		Fork size	L × W × T	mm	1070 × 100 × 40		1070 × 122 × 40	
6		Mast tilt angle	FR/RR	°	6.5/6.5	6.5/6.5	6.5/6.5	
7		Minimum turning radius		mm	1550	1550	1680	
8		Minimum right angle stacking aisle width		mm	3070	3070	3220	
9		Minimum ground clearance		mm	102	102	100	
10		Height of overhead guard		mm	1960	1960	2020	
11	Performance	Maximum travel speed	Full load	km/h	14	14	13	
12		Maximum lift speed	Full load	mm/s	260	260	200	
13		Maximum gradeability		%	15	15	15	
14	Dimensions	Overall length	Without forks	mm	1930	1930	2080	
15		Overall width		mm	1066	1066	1156	
16	Power	Self weight	Without load	kg	3200	3260	3550	
17		Battery	Voltage/capacity	V/Ah	48/500	48/500	48/560	
18		Motor	Traveling	KW	4.8 × 2	4.8 × 2	4.8 × 2	
19			Lifting	KW	10	10	10	
20		Way of control			AC	AC	AC	
21		Operating pressure			Mpa	15.5	15.5	15.5
22		Maximum drawbar pull			KN	18	18	14

The company reserves the right to change the parameters without notice.



ADDRESS: SHANGHAI ROAD, BAOHE INDUSTRIAL PARK, HEFEI, ANHUI, CHINA PC. 230051

TEL: 86-551-62297986

FAX: 86-551-62297990

WEB: www.jaczg.com ; www.jacforklift.com

E-mail: jac@jaczg.com

All Rights Reserved by JAC heavy duty co.,ltd. Parameter updating without notice, the picture just for reference. 2020/05/28